# Trademark Transfers

## TECHNICAL DATASHEET

www.ja-int.com

APPLICATION

| | | |
|---|---|---|
| Temperature (°C): | 210°C | |
| Temperature (°F): | 410°F | |
| Time: | 7-10 seconds | |
| Pressure: | High | 56.9 - 71.1 psi / 3.9 - 4.9 bar / 4.0 - 5.0 kg/cm2 |

This product may leave behind a small amount of residual ink on the carrier.

LAUNDERING
Suitable for Industrial Laundering up to 85°C
Suitable for Industrial Drying Techniques - Medium
Suitable for Dry-Cleaning
Iron - Medium, On Reverse

HANDLING AND STORAGE
Store in a cool, dry environment
Keep away from direct sunlight
No personal protection equipment is required in handling and storage

COMPOSITION
Ink - Plastisol
Carrier - Offset Paper

HEALTH & SAFETY
This product is identified as Non-Hazardous to the end user
No PPE is required during application**

ENVIRONMENTAL / RECYCLING
Carrier paper - widely recycleable

**Any fumes created by this transfer during application are harmless. However, modern garment materials can be coated and finished in many different ways; some of which may alter their application and health & safety requirements. We recommend thorough checking and testing of any garment material to determine the correct requirements before application.