Ultima Stitchmax

TECHNICAL DATASHEET

www.ja-int.com

APPLICATION

Temperature (°C):	200°C	
Temperature (°F):	392°F	
Time:	12 seconds	
Pressure:	High	56.9 - 71.1 psi / 3.9 - 4.9 bar / 4.0 - 5.0 kg/cm2
Carrier Release:	N/A	

LAUNDERING
Suitable for Industrial Laundering up to 85°C
Suitable for Industrial Drying Techniques - Medium
Suitable for Dry-Cleaning
Iron - Medium, On Reverse
Do Not Bleach
Do Not wash with strong Acid or Alkaline additives

HANDLING AND STORAGE
Store in a damp-free environment at a stable temperature of ~20°C
Keep away from direct sunlight
No personal protection equipment is required in handling and storage

COMPOSITION
Base - Fabric with Solvent ink coating
Adhesive - Polyester
Print - UV Cure
Carrier - N/A

HEALTH & SAFETY
This product is identified as Non-Hazardous to the end user
No PPE is required during application**

ENVIRONMENTAL / RECYCLING
Non-Recyclable
Compostable

CERTIFICATION
Wash Stability: EN ISO 15797

**Any fumes created by this transfer during application are harmless. However, modern garment materials can be coated and finished in many different ways; some of which may alter their application and health & safety requirements. We recommend thorough checking and testing of any garment material to determine the correct requirements before application.